

DrillNow™ Shale Unihead™ (UH-S)

Delivering Superior Service. Wellhead experts since 1930

Realize increased reliability and productive time on the pad with our Shale Unihead (UH-S) system.

The UH-S was developed to bring the benefits of Unihead technology to shale applications. The UH-S features our standard hanger and lock ring packoff technology increasing productive time and enhancing safety on the pad. The UH-S is optimized for Surface x Intermediate x Production Casing well designs and utilizes our standard Unihead production casing hangers and packoffs ensuring availability and improving operational reliability.




Speed

- ▶ Saves up to 30 hours of rig time
- ▶ SWC BOP Quick Connect available
- ▶ Offline cementing, every string
- ▶ Offline BOP testing



Operational Performance

- ▶ Field proven performance
- ▶ Internal Lock Ring hanger retention
- ▶ Detailed installation procedures
- ▶ Experienced service personnel



Versatility

- ▶ Installation through riser or rotary table
- ▶ Ability to rotate production casing hanger
- ▶ Drill for liner without BOP break



Applications

- ▶ 13 5/8" BOP
- ▶ Surface casing- 10 3/4" - 13 3/8"
- ▶ Intermediate casing - 7 5/8" -9 5/8"
- ▶ Production casing- 4 1/2" -7 5/8"
- ▶ Drilling pressures- 5K & 10K
- ▶ Completion pressures-10K & 15K



Safety

- ▶ Eliminates work below suspended loads
- ▶ Reduced wellhead penetrations
- ▶ BPV profile on production hanger
- ▶ Reduced time in cellar