

Ordering Information

Size	Model Number	ANSI Flange	Max. W.P.	Trim	Full Open		Stock Number	Weight
					Cv	Cg		
2"	DFG-202-436	150 lb. RF	275 psi	1-1/4" Throttling	19.0	660	80003668	70
				1-3/4" Throttling	36.0	1200	80003691	
				1-3/4" Quick Opening	36.0	1200	80003692	
2"	DFG-214-436	600 lb. RF	1440 psi	1-1/4" Throttling	19.0	660	80003684	70
				1-3/4" Throttling	36.0	1200	80003693	
				1-3/4" Quick Opening	36.0	1200	80003694	
2"	DFG-214R-436	600 lb. RTJ	1440 psi	1-1/4" Throttling	19.0	660	80003688	70
				1-3/4" Throttling	36.0	1200	80003695	
				1-3/4" Quick Opening	36.0	1200	80003696	

Differential Pressure Capability and Actual Diaph. Pressure Ranges

Spring Precompression	Trim Size	Flow Over the Seat	Flow Under the Seat
Normal Spring Pre-load 9/32" Comp.	1 1/4	180 psi 9 - 15	120 psi 0 - 15
	1 3/4	180 psi 9 - 15	60 psi 0 - 15
Maximum Spring Pre-load 1" Comp	1 1/4	360 psi 0 - 23	450 psi 0 - 20
	1 3/4	360 psi 0 - 23	300 psi 0 - 23

Caution: Do not exceed Valve Working Pressure.
See Ordering Chart Above

Dimensions

Model No.	A	B
DFG-202	15-1/6"	10"
DFG-214	15-1/6"	11-1/4"
DFG-214R	15-1/6"	11-3/8"

